


# Cold Water Electric Belt Drive

## CW Premium Series

The stationary version of the CW electric series is designed for wash bays, golf courses and restaurant applications where mobility isn't necessary. The stainless-steel package design ensures longevity even in the toughest environments.



CW-2004-SME1 shown with standard low pressure detergent injector



Belt drive triplex piston General pump with ceramic plungers accepts incoming water up to 175° F

### Pump

- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- In-line water strainer
- Quick connect low pressure detergent injection
- Bypass system

### Motor

- Open drip-proof motor (1000 & 3000-PSI models)
- Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models)
- 4-foot electrical cord with ground fault circuit interrupter (NEMA 5-20P, 20-amp plug on CW-1003-SME1)

### Frame

- Stainless-steel base and frame
- Removable panel for pump access
- Easy-to-access cabinet design
- Four rubber isolators

### Components

- Dual cogged belt drive system for increased belt life
- Conveniently located on/off switch
- Time delay shutdown will shut unit off automatically when trigger gun is released and timer reaches setting

### Unit Includes

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x 3/8-inch pressure hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

### Warranties



CW-2004-SME3 shown on optional stainless-steel wall mounting bracket (AW-9501-0000)

Model Number	PSI	GPM	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CW-1003-SME1	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	29.5in.x20.5in.x15in.	222 lbs.	172 lbs.
CW-2004-SME1	2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	NEMA 6-30P	29.5in.x20.5in.x15in.	272 lbs.	214 lbs.
CW-2004-SME3	2000	3.9	6.0 HP, 230V, 3Ø, 15.0A	NEMA L15-20P	29.5in.x20.5in.x15in.	262 lbs.	204 lbs.
CW-3004-SME3	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	NEMA L15-30P	29.5in.x20.5in.x15in.	292 lbs.	234 lbs.

### ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
AW-9501-0000	<b>Stainless-steel wall mounting bracket</b> - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0000	<b>Powder coated steel wall mounting bracket</b> - Provides a permanent location for your pressure washer in a shop or plant facility	All models
CX-0069	<b>Auto start/stop</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled unit will restart	All models
CX-0076	<b>460V, 3-phase models</b> - For when you have 460V of power available	CW-2004-SME3
CX-0077	<b>460V, 3-phase models</b> - For when you have 460V of power available	CW-3004-SME3
CX-0078	<b>Remote box</b> - Adds control box which may be mounted away from unit to control on/off, N/A on models with auto start/stop	All models
CX-0087	<b>208V, single-phase</b> - For when you have 208V of power available	CW-2004-SME1
CX-0088	<b>208V, 3-phase models</b> - For when you have 208V of power available	CW-2004-SME3
CX-0090	<b>208V, 3-phase models</b> - For when you have 208V of power available	CW-3004-SME3