

Cold Water Gasoline Belt Drive

CWC Premium Series

The Mi-T-M CWC Series pressure washers are built for continuous heavy-duty cleaning with an 8-hour run time and up to 6000-PSI. One of the most powerful cold water pressure washers on the market today, this unit is jobsite-site ready with 1¼-inch roll cage, handles and lifting hook.



CWC-5004-3MAH
CWC-5004-3MGH
CWC-5005-3MGH



CWC-5004-3MAH



11.5-gallon capacity fuel tank allows for 8-hour running time

Pump

- Belt drive triplex piston AR or General pump with ceramic plungers
- Preset stainless-steel and brass unloader
- Forged brass manifold
- Thermal and safety relief valves
- Water filter with clear sleeve for screen inspection (High capacity water filter on 3000-PSI model)
- Pump oil drain

Engine

- Performance-proven engine with low-oil protection
- Electric start (battery included)
- Engine oil drain

Frame

- Patented frame design includes powder coated steel frame with 1¼-inch roll cage, handles and lifting hook
- Two-piece belt guard with ¼-turn release for quick access to belts
- Convenient gun/wand holder and hose wrap
- Solid steel threaded axles
- Pneumatic mag tires with tubes with locking tire brake

Components

- Heavy-duty dual cogged belt drive system for increased belt life
- Easy start valve
- Polyethylene fuel tank will not rust

Unit Includes

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x ¾-inch non-marking hose with quick connects, swivel and bend restrictors (½-inch on 3000-PSI model)
- Professional-grade insulated trigger gun with safety lock-off
- 48-inch lance with rubber grip

Warranties



Model Number	PSI	GPM	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CWC-3008-3MGH	3000	8.0	688cc Honda OHV	43in.x27.75in.x36in.	511 lbs.	388 lbs.
CWC-5004-3MAH*	5000	4.0	688cc Honda OHV	43in.x27.75in.x36in.	501 lbs.	378 lbs.
CWC-5004-3MGH	5000	4.0	688cc Honda OHV	43in.x27.75in.x36in.	501 lbs.	378 lbs.
CWC-5005-3MGH	5000	5.0	688cc Honda OHV	43in.x27.75in.x36in.	511 lbs.	388 lbs.
CWC-6004-3MGH	6000	3.7	688cc Honda OHV	43in.x27.75in.x36in.	511 lbs.	388 lbs.

*Model equipped with AR pump, all other models equipped with General pumps.

OPTION

Part Number	Description	Fits Models
TX-1304-M	Puncture-proof tires - Tires are flat-free and maintenance-free, 13-inch, white hub, four tires	All models