

Propane Forced Air

Our hand carry propane forced air heaters feature enclosed gas controls and heavy-duty steel construction. Ready to use - just connect to propane cylinder and plug-in.



CSA
CERTIFIED



Important Notes

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

All Models Feature Frame

- Heavy-duty steel construction
- Easy-lift handle for portability at home or on the jobsite
- Adjustable height angle (except on MH-0375 model)

Heat Output

- Variable BTUs (MH-0050-LM10 & MH-0150-LM10)

Components

- High performance fan
- Automatic shut-off if power is interrupted or flame is extinguished
- Enclosed gas controls
- Electronic ignition
- Propane inlet connector - connects heater to propane tank via a supply hose
- 10-foot hose and regulator (Not available on MH-0150-NM10)
- One touch ignition and heat control for easy operation

MH-0050 Model Features

Propane

- Will operate on 20 lb. cylinder

150,000 to 375,000 BTU Models Feature

Heat Output

- Adjustable thermostat (MH-0150-LM10, MH-0150-NM10 and MH-0375-LM10)

Warranty on All Models



For use in workshops, garages, construction sites and farms with proper ventilation.



MH-0375-LM10



Model Number	MH-0050-LM10	MH-0150-LM10	MH-0150-LM10*	MH-0150-NM10*	MH-0375-LM10*
Heat Output	50,000 BTU	120-135-150,000 BTU	150,000 BTU	150,000 BTU	375,000 BTU
Hot-Air Flow	300 CFM	400 CFM	400 CFM	435 CFM	1,500 CFM
AC Power	120V, 60Hz, Less than 1.0 Amp	120V, 60Hz, Less than 1.0 Amp	120V, 60Hz, Less than 1.0 Amp	120V, 60Hz, Less than 1.0 Amp	120V, 60Hz, 1.45 Amp
Motor Size	1/10 HP	1/9 HP	1/9 HP	1/9 HP	1/5 HP
Fuel	Propane	Propane	Propane	Natural Gas	Propane
Fuel Consumption	2.3 lbs./hr.	5.5/6.2/6.9 lbs./hr.	6.9 lbs./hr.	150 cu. ft./hr.	17.3 lbs./hr.
Required Cylinder Size	20 lbs.	100 lbs.	100 lbs.	N/A	(2) 100 lbs.
Max. Operating Hours (per required cylinder size)	11.0 hours	18.0 hours	18 hours	N/A	11.5 hours
Heating Area	1,000 sq. ft.	3,800 sq. ft.	3,800 sq. ft.	3,800 sq. ft.	9,000 sq. ft.
Dimensions (LxWxH)	18.1in.x7.7in.x12.8in.	25.1in.x9in.x15.5in.	25.1in.x9in.x15.5in.	25.1in.x9in.x15.5in.	34in.x12.6in.x18.5in.
Ship Wt.	19 lbs.	29 lbs.	29 lbs.	35 lbs.	49 lbs.
Net Wt.	15 lbs.	23 lbs.	23 lbs.	24 lbs.	41 lbs.

*Models include thermostat.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.