

Dual-Axle Water Trailer

The Mi-T-M dual-axle 510-gallon water trailer is perfect for controlling dust on jobsites and parking lots, heavy equipment cleaning, street cleaning, firefighting and a host of other applications. This tough trailer offers rear spray, fire and garden hose hook-ups and hydrant fill capabilities. Pair it with a 2-inch centrifugal pump featuring 118cc Honda OHV engine and it is ready to tackle any job requiring portable water.



MWT-0510-2MHD (Dual-axle trailer with 510-gallon water tank and 2-inch centrifugal pump)

Tank

- 510-gallon elliptical low profile 3/8-inch thick polyethylene
- 16-inch manhole with 4-inch vent and a sump drain
- Lid is tethered

Pump

- 2-inch centrifugal pump featuring 118cc Honda OHV engine with low oil shutdown
- Precision molded aluminum

Control Manifold

- Easy to operate butterfly brass valves

Plumbing

- Dual rear spray heads
- Garden hose connector
- Rear drain
- Manifold discharge system
- Water hammer prevention valve

Bed

- 5-foot x 8-foot frame

Trailer

- DOT approved
- Trailer dimensions: 13'7" x 82" x 70"
- 12-inch underclearance at axle, no plumbing beneath the trailer deck
- (2) 3,500-lb. tandem axles with hydraulic surge brakes
- (4) ST225-75 15-inch tires with white spoke rims
- (2) fenders
- 2 5/8-inch coupler with 7,000-lb. capacity
- 7,000-lb. side-mount crank jack
- Dual leaf spring suspension
- Rubber mounted sealed lights
- Wire storage basket
- Two safety chains with snap hooks
- 7,000-lb. gross vehicle weight
- Trailer weight: 1,580-lbs. empty/5,900-lbs. loaded

Warranties

| | | | |
|--|---|---|---|
| 1 YEAR LIMITED TRAILER WARRANTY | 2 YEAR LIMITED PUMP WARRANTY | 3 YEAR LIMITED HONDA ENGINE WARRANTY | 3 YEAR LIMITED WATER TANK WARRANTY |
|--|---|---|---|



1 1/2-inch fire hose hook-up with 50-foot x 1 1/2-inch hose and fog nozzle



Break-away hydrant fill with 25-foot x 2 1/2-inch hose



Due to advancements in technology, the design of Mi-T-M trailers may change after the publication of this catalog.