

# Two Stage Gasoline

## 20-Gallon

If you're in the market for power then this air compressor will meet all your needs. Strong and durable, quick and efficient, it is built of cast iron and stainless-steel and can store ample pressure with its powder coated ASME 20-gallon receiver tank. Portable or stationary, this unit will deliver.



AM2-PH09-20M



AM2-SH09-20M shown with optional electric start (AX-0015)

### All Models Feature Compressor Pump

- Quality cast iron two stage compressor with venting system for reduced crankcase temperature and pressure
- Splash lubricated cast iron crankcase to extend the hours of performance
- Cast iron head for heat dissipation
- Stainless-steel braided discharge hose
- Large canister intake filter

### Engine

- Industrial Honda OHV (Electric start optional)
- Pneumatic idle control to conserve fuel
- Engine oil drain

### Frame

- Powder coated ASME coded 20-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts

### PORTABLE MODEL

Model Number	CFM @ PSI	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM2-PH09-20M	17.2 @ 175	270cc Honda OHV	46in.x26in.x39.5in.	356 lbs.	306 lbs.

### STATIONARY MODEL

Model Number	CFM @ PSI	Displacement/Engine	Dimensions (LxWxH)	Bolt Down (LxW)	Ship Wt.	Net Wt.
AM2-SH09-20M	17.2 @ 175	270cc Honda OHV	37in.x18in.x38in.	23.193in.x11in.	356 lbs.	306 lbs.

### ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
AW-0007-0196	Rear lifting handle (N/A for models with electric start options) - Allows unit to be lifted from both ends	AM2-PH09-20M
AX-0003	Manual drain metal bowl - Drains moisture from air system	All models
AX-0015	Electric start (battery and cables not included) - For easy starting	AM2-SH09-20M
AX-0017	Electric start (battery and cables included) - For easy starting	All models
Consult Factory	Cable throttle control - Automatically throttles down engine to conserve fuel	All models
TX-1302-W	Puncture-proof tires - Tires are flat-free, maintenance-free, 13-inch, white hub, two tires	AM2-PH09-20M

### Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- Belt tightening system pulls engine straight to ensure constant belt alignment
- 16.5-inch fly wheel for extra cooling and longer life
- Quality pilot valve unloader

### AM2-PH09-20M Model Additional Features

#### Frame

- Convenient lifting handles
- Two pneumatic tires with tubes and steel hubs

### Warranties for All Models

**2**  
YEAR  
LIMITED  
PUMP EXCHANGE  
WARRANTY

**3**  
YEAR  
LIMITED  
HONDA ENGINE  
WARRANTY

See page 51 for more information